

TDD-PTM-SKD170

17" PCAP Touch Display Modules



Overview

The **TDD** PTM-TDM series comes with industrial grade LCD display and project capacitive touch. It is also available with flexible options for LCD screens enhanced treatment such as **Anti-glare** surface treatment and **Optical Bonding** solution, delivers an industrial, reliable and cost-effective solution with outstanding image clarity & accurate touch response for OEMs & systems integrators. 7-98" sizes with rugged bezel & flat structure (**optional**), high durability and versatility for embedded applications which customers have maximum flexibility for mechanical design.

Features

- Touch thru glass (**optional for AG & Anti-mist Optical Bonding**) enabled with PCAP supports thickness up to 5mm
- Composed by **Industrial(optional)** TFT-LCD, CTP / AD / TP Board & power supply with cables and USB cables
- IP65 (front) for water and dust protection, flexible mounting in any table, kiosk, or cabinet design

Specifications

Panel

Diagonal Size	17"(4:3), 43cm, Active matrix TFT LCD (LED)
Active Area (mm)	338.92 mm x 271.34 mm
Resolution	1280 x 1024
Viewing Angle	Horizontal: 85° or 170° total / Vertical: 80° or 160° total
Number of Colors	16.7 million
Brightness (typical)	250 nits
Response Time-total	30 (Typ.)(Tr+Td) ms
Contrast Ratio	1000:1
Input Video Frequency	Horizontal: 30 - 60 KHz / Vertical: 50 - 75 Hz

Touch

Touch Technology	PCAP (Projected Capacitive) - 10 Touch Capacity
Surface Treatment	Water, Dust & Vandal proof; Optional : Anti-glare, Anti-fingerprint, Anti-smudge, Anti-bacterial
Supported OS	Windows / Android / Linux / Mac

Interfaces / Connectors / Controls

Video Interfaces	VGA x1 / HDMI x1 / DVI x1 (opt.) / Display Port x1 (opt.) / USB x1 for Touch; HDCP: Yes
Connectors & Controls	Audio Mini jack x1 / DC x1; 5 OSD buttons

Power Supply / Consumption: 100-240 VAC / 12VDC +/- 5%; 20W typical, 1.5W sleep, 0.5W off

Mechanical Product Dimensions: 383.7x316x57(**A**) | 51(**S**)mm / Weight(Unpacked / Packed): 3.9 / 5.35 kg
Box Dimensions: 530 x 431 x 141mm / VESA Mounting: 75 x 75 / 100 x 100mm

Environmental Operating / Storage Temperature: -10°C to 50°C / -20°C to 60°C

Accessories Power adapter / cable, HDMI / VGA / Touch USB cable, flush mount brackets w/screws (opt.)

Others MTBF / Warranty / Enclosure Color: 50,000 hours demonstrated / 1-year / black | silver
Ready for Use: 24/7, **A** = Aluminum Back, **S** = Steel Back in above "**Mechanical**"

* **TDD** (www.tddtouch.com, sales@tddtouch.com) reserves the right to change specifications without prior notice.