

# TDD-OFTM-BF70C

## 7" **Industrial** Bezel-free (Rear Mount) Open Frame PCAP Touch Monitors



### Overview

The **TDD Touch Monitors** include **Standard, Industrial (Open Frame Bezel-free | Rear Mount, Panel Mount, Closed Frame), Outdoor, Waterproof, Stainless Steel, Marine, Curved, Desktop POS, Commercial Displays, Medical and Custom** types, delivers an industrial, reliable and cost-effective solution with outstanding image clarity & accurate touch response for OEMs & systems integrators. 7-98" sizes with rugged bezel, flat structure, high durability and versatility for Kiosks applications from Self-service, Automated Parking, Industrial Automation, Outdoor Control, Healthcare to Gaming.

### Features

- Touch thru glass enabled with PCAP supports thickness up to 5mm
- Embedded design with **Rugged TFT Panel, Sturdy Aluminum Front Frame & Steel Back**
- IP65 (front) for water and dust protection, flexible mounting in any table, kiosk, or cabinet design

### Specifications

#### Panel

Diagonal Size	7"(16:9), 17.78cm, Active matrix TFT LCD (LED)
Active Area (mm)	154.0 mm x 85.92 mm
Resolution	1024 x 600
Viewing Angle	Horizontal: 85° or 170° total / Vertical: 85° or 170° total
Number of Colors	16.7 million
Brightness (typical)	250 nits
Response Time-total	13 (Typ.)(Tr/Td) ms
Contrast Ratio	800:1
Input Video Frequency	Horizontal: 30 - 60 KHz / Vertical: 50 - 75 Hz

#### Touch

Touch Technology	PCAP (Projected Capacitive) - 10 Touch Capacity
Surface Treatment	Water, Dust & Vandal proof; <b>Optional:</b> Anti-glare, Anti-fingerprint, Anti-smudge, Anti-bacterial
Supported OS	Windows / Android / Linux / Mac

#### Interfaces / Connectors / Controls

Video Interfaces	VGA x1 / HDMI x1 / DVI x1 (opt.) / Display Port x1 (opt.) / USB x1 for Touch; HDCP: Yes
Connectors & Controls	Audio Mini jack x1 / DC x1; 5 OSD buttons

#### Power

Supply / Consumption: 100-240 VAC / 12VDC +/- 5%; 10W typical, 1.2W sleep, 0.5W off

#### Mechanical

Product Dimensions: 190.5 x 125 x 40mm / Weight (Unpacked / Packed): 2 / 2.3kg  
Box Dimensions: 320.3 x 255 x 170mm / VESA Mounting: 75 x 75 / 100 x 100mm

#### Environmental

Operating / Storage Temperature: -10°C to 50°C / -20°C to 60°C

#### Accessories

Power adapter / cable, HDMI / VGA / Touch USB cable, flush mount brackets w/screws (opt.)

#### Others

MTBF / Warranty / Enclosure Color: 50,000 hours demonstrated / 1-year / black | silver  
Ready for Use: 24/7

\* TDD ([www.tddtouch.com](http://www.tddtouch.com), [sales@tddtouch.com](mailto:sales@tddtouch.com)) reserves the right to change specifications without prior notice.