TDD-PTM-C236CA 23.6" LED Framed C Curved

PCAP Touch Monitors





Overview

The **TDD** curved touch monitors (VESA mount) with C-type / J-type format, Non-LED / LED Framed design and desktop / wall mount installation, which provides impressive visual experience with accurate touch response that is attractive and reliable especially for game players. It is available in a wide range of sizes (23.6" to 55"), offering the versatility in the area of gaming, casino and sports betting.

Features

- Touch (optional for no touch) thru glass enabled with PCAP with Customized LED Tiles for casino slot machines
- Comfortable Viewing Experience with R1500 / R1800 Ratio and 2 / 2.5 /4K Resolution with excellent image clarify

23.6"(16:9), 59.944cm, Active matrix TFT LCD (LED)

• Outstanding Industrial-grade design with High-end Sturdy Steel / Aluminum Frame

521.395 mm x 293.284mm

Specifications

Diagonal Size

Active Area (mm)

	_		_
_	٠.	n	Δ I

Resolution	1920 x 1080		
Viewing Angle	Horizontal: 89° or 178° total / Vertical: 89° or 178° total		
Number of Colors	16.7 million		
Brightness (typical)	250 nits		
Response Time-total	10 (Typ.)(G to G) ms		
Contrast Ratio	3000:1		
Touch			
Touch Technology	PCAP (Projected Capacitive) - 10 Touch Capacity		
Surface Treatment	Water, Dust & Vandal proof; Optional: Anti-glare, Anti-fingerprint, Anti-smudge, Anti-bacterial		
Supported OS	Windows / Android / Linux / Mac		
Others	Hot-bending process / TP Thickness: 2.55mm (±0.3mm) / Light Transmission: ≥85%		
Interfaces / Connectors / Controls			
Interfaces&Connectors	VGA x1 / HDMI x1 / USB x1 for Touch / DC x1 / Audio x1; 5 OSD buttons		
LED Parameters	RGB colorful effect; atmosphere light mode: solid color, marquee, water, breathing, gradient mode on the Front / Side / Back(with Programmable Controller)		
Power	Supply / Consumption: 100-240 VAC / 12VDC +/- 5%; 25W typical, 1.5W sleep, 0.5W off		
Mechanical	Product Dimensions: 598.63 x 365.78 x 88.91 / Weight (Unpacked / Packed): 8.2 / 9.2kg Box Dimensions: 696 x 468 x 260mm / VESA Mounting: 140 x 180mm		
Environmental	Operating / Storage Temperature: -10°C to 50°C / -20°C to 60°C		
Accessories	Power adapter / cable, HDMI / VGA / Touch USB cable, VESA mount kits w/screws (opt.)		
Others	MTBF / Warranty / Enclosure Color: 50,000 hours demonstrated / 1-year / black white Ready for Use: 24/7, Curvature: R1500		

^{*} TDD (<u>www.tddtouch.com</u>, <u>sales@tddtouch.com</u>) reserves the right to change specifications without prior notice.