


## TDD-DTM860

### 86 '' Digital Signage Closed Frame PCAP Touch Monitors



#### Overview

The **TDD Touch Monitors** include **Standard, Industrial (Open Frame Bezel-free | Rear Mount, Panel Mount, Closed Frame), Outdoor, Waterproof, Stainless Steel, Marine, Curved, Desktop POS, Commercial Displays, Medical** and **Custom** types, delivers an industrial, reliable and cost-effective solution with outstanding image clarity & accurate touch response for OEMs & systems integrators. 7-98" sizes with rugged bezel, flat structure, high durability and versatility for Kiosks applications from Self-service, Automated Parking, Industrial Automation, Outdoor Control, Healthcare to Gaming.

#### Features

- Touch thru glass enabled with PCAP supports thickness up to 5mm
- Desktop or wall mount design with **Light Aluminum Frame & Steel Back**
- IP65 (front) for water and dust protection, flexible mounting in any table, kiosk, or cabinet design

#### Specifications

##### Panel

Diagonal Size	86"(16:9), 218.44cm, Active matrix TFT LCD (LED)
Active Area (mm)	1895.2 mm x 1065.6 mm
Resolution	<b>3840 x 2160</b>
Viewing Angle	Horizontal: 89° or 178° total / Vertical: 89° or 178° total
Number of Colors	16.7 million
Brightness (typical)	350 nits
Response Time-total	8 (Typ.)(G to G) ms
Contrast Ratio	5000:1
Input Video Frequency	Horizontal: 30 - 60 KHz / Vertical: 50 - 75 Hz

##### Touch

Touch Technology	PCAP (Projected Capacitive) - 10 Touch Capacity
Surface Treatment	Water, Dust & Vandal proof; <b>Optional:</b> Anti-glare, Anti-fingerprint, Anti-smudge, Anti-bacterial
Supported OS	Windows / Android / Linux / Mac

##### Interfaces / Connectors / Controls

Video Interfaces	VGA x1 / HDMI x1 / DVI x1 (opt.) / Display Port x1 (opt.) / USB x1 for Touch; HDCP: Yes
Connectors & Controls	Audio Mini jack x1 / DC x1; 5 OSD buttons

##### Power

Supply / Consumption: 100-240 VAC / 12VDC +/- 5%; 350W typical, 1.5W sleep, 0.5W off

##### Mechanical

Product Dimensions: 1968 x 1177.5 x 92.9mm / Weight (Unpacked/Packed): 62.7/71.1kg  
Box Dimensions: 2110 x 225 x 1325mm / VESA Mounting: 600 x 600mm

##### Environmental

Operating / Storage Temperature: -10°C to 50°C / -20°C to 60°C

##### Accessories

Power adapter / cable, HDMI / VGA / Touch USB cable, wall mount brackets w/screws (opt.)

##### Others

MTBF / Warranty / Enclosure Color: 50,000 hours demonstrated / 1-year / black | silver  
Ready for Use: 24/7

\* TDD ([www.tddtouch.com](http://www.tddtouch.com), [sales@tddtouch.com](mailto:sales@tddtouch.com)) reserves the right to change specifications without prior notice.