# TDD-CP-SOK236MCB-D 23.6" Desktop Slim Curved Self-Ordering Kiosks with Orange Strip





## Overview

The TDD Self Ordering Kiosks include Slim Curved, Sleek Curved, Slim, Easy and Android Self-checkout types, which are designed to adapt to changing consumer demands in retail environments. These modular and reliable kiosks support self-ordering, self-checkout, and visitor check-in, empowering customers to control their experience. Equipped with Receipt Printer, high-precision QR Code reader, ID Camera and optional functions like RFID, Fingerprint scanning, Metal keypads, Bill & Coin Recycler (Custom) and TDD's innovative technology, it is the perfect solution for seamlessly integrating modern businesses to these user-friendly kiosks to enhance customer satisfaction and operational efficiency.

### Features

- Robust construction ensures continuous use in unattended areas.
- Modular design minimizes total cost of ownership while maximizing operational efficiency.
- Compact design for space-restricted environments with middle hollow LED and orange decorative edge strips

### **Specifications**

#### System (3.5" Motherboard: 5.7 x 4inch=146 x102mm) Processor Android: RK3188/RK3288/RK3566/RK3568 Quad-core Cortex-A9/A17/A55 1.6/1.8/ 2.0GHz Windows: Intel® J1900 / J4125 Quad Core 2.0 / 2.7GHz / Intel® Core™ i3 / i5 / i7 / i9 4-13<sup>th</sup>G Android: 1 / 2GB(std) / 4 / 8 / 16GB; Windows: DDR3/4 2 / 4(std) / 8 / 16 / 32 / 64GB Memory(RAM) Android: 4/8/16(std)/32/64GB eMMC Flash; Windows: 32/64(std)/128/256/512GB SSD/HDD Storage Panel (Non-LED | LED Framed, C curved, Aluminum | Steel Frame, Curvature: R1500) Size / Active Area (mm) 23.6"(16:9), 59.944cm, Active matrix TFT LCD (LED) / 521.395 mm x 293.284mm **Resolution / Contrast** 1920 x 1080 / 3000:1 Horizontal: 89° or 178° total / Vertical: 89° or 178° total Viewing Angle Color Depth/Brightness 16.7 million / 350 nits Response Time / Freq 10 (Typ.)(Tr+Td) ms / Horizontal: 30 - 60 KHz / Vertical: 50 - 75 Hz Touch Touch Technology / OS PCAP (Projected Capacitive) - 10 Touch Capacity / Windows / Android / Linux / Mac

Surface Treatment	Water, Dust & Vandal proof; Optional: Anti-glare, Anti-fingerprint, Anti-smudge, Anti-bacterial			
I / O Ports				
Android	USB x2 / HDMI x1 / LAN x1 / WIFI x1 / DC x1 / TF-CARD x1 / Audio x1			
Windows	USB x4 / COM x2 / VGA x1 / HDMI x1 / LAN x1 / WIFI x1 / DC x1 / Audio x1 / Mic x1			
Power	Supply / Consumption: 100-240 VAC / 12VDC 5A +/- 5%; 25W typical, 1.2W sleep, 0.5W off			
Mechanical	Product Dimensions (HxWxD): N/Amm/Weight(Unpacked/Packed): N/A kg Box Dimensions: N/A mm / VESA Mounting: N/A			
Environmental	Operating / Storage Temperature: -10°C to 50°C / -20°C to 60°C			
Accessories	Power adapter / cable, free standing / wall mount mounting kits w/screws (opt.)			
Others	MTBF / Warranty / Enclosure Color / Ready for Use: 50,000 hours / 1-year / white black / 24/7 <b>Speakers:</b> Internal, $8\Omega$ / 2W x 2			
Optional Peripherals (Default: Marked by Yellow)	Receipt Printer: thermal, 150mm/s, 80mm printing width, auto cut, paper end detection, USB QR / Barcode Scanner: 1D / 2D, CMOS with 640 x 480 (opt. for 752 x 480) pixel, USB ID Camera: 2 / 5MP , monocular / binocular cameras, USB RFID: 13.56M Hz Mifare ISO14443A read only, USB POS Holer: Yes Fingerprint Scanner: Custom, USB Metal Keypad: Custom, 16 keys, USB 4G: Mini-PCIe, GPS: TTL / USB or 4G & GPS: Mini-PCIe			
No.				
Thermal Printer	Barcode Scanner	Camera	RFID Card Reader	Fingerprint Sensor
Keyboard	WIFI Antenna	4G LTE Module	GPS	More Peripherals

**Dimensions**