

TDD-PTM-PM190WP

19" **Waterproof** Panel Mount (Front Mount) PCAP Touch Monitors



Overview

The **TDD Touch Monitors** include **Standard, Industrial (Open Frame Bezel-free | Rear Mount, Panel Mount, Closed Frame), Outdoor, Waterproof, Stainless Steel, Marine, Curved, Desktop POS, Commercial Displays, Medical and Custom** types, delivers an industrial, reliable and cost-effective solution with outstanding image clarity & accurate touch response for OEMs & systems integrators. 7-98" sizes with rugged bezel, flat structure, high durability and versatility for Kiosks applications from Self-service, Automated Parking, Industrial Automation, Outdoor Control, Healthcare to Gaming.

Features

- Touch thru glass (with **Anti-mist Optical Bonding**) enabled with PCAP supports thickness up to 5mm
- Embedded design with **Rugged TFT Panel, Sturdy Aluminum Enclosure with External Connected OSD**
- **IP65 Fully Enclosed Fanless Design with M12 Metal I/O Connectors**, flexible mounting in any table, kiosk or cabinet

Specifications

Panel

Diagonal Size 19"(4:3), 48.26cm, Active matrix TFT LCD (LED)

Active Area (mm) 377.32 mm x 302.06 mm

Resolution 1280 x 1024

Viewing Angle Horizontal: 89° or 178° total / Vertical: 89° or 178° total

Number of Colors 16.7 million

Brightness (typical) **250 nits (Optional: 500 / 1000 nits)**

Response Time-total 14 (Typ.)(Tr+Td) ms

Contrast Ratio 1000:1

Input Video Frequency Horizontal: 30 - 60 KHz / Vertical: 50 - 75 Hz

Touch

Touch Technology PCAP (Projected Capacitive) - 10 Touch Capacity (**Optional: Waterproof Firmware**)

Surface Treatment Water, Dust & Vandal proof; **Optional:** Anti-glare, Anti-fingerprint, Anti-smudge, Anti-bacterial

Supported OS Windows / Android / Linux / Mac

Interfaces / Connectors / Controls

Video Interfaces HDMI x1 / USB x1 for Touch; HDCP: Yes

Connectors & Controls DC x1; Key x1 (5 External Connected OSD)

Power

Supply / Consumption: 100-240 VAC / 12VDC +/- 5%; 17W typical, 1.5W sleep, 0.5W off

Mechanical

Product Dimensions: 425.1 x 353.1 x 40mm / Weight (Unpacked/Packed): 11.2 / 12.7 kg
Box Dimensions: 500 x 160 x 420mm / VESA Mounting: 75 x 75 / 100 x 100mm

Environmental

Operating / Storage Temperature: **-10°C to 50°C (Opt. for -20°C to 70°)** / -20°C to 60°C

Accessories

Power adapter / cable, HDMI / VGA / Touch USB cable, panel mount kits w/screws (opt.)

Others

MTBF / Warranty / Enclosure Color: 50,000 hours demonstrated / 1-year / black | silver
Ready for Use: 24/7

* TDD (www.tddtouch.com, sales@tddtouch.com) reserves the right to change specifications without prior notice.