TDD-PTM-LFC490J 49" LED Framed J Curved

PCAP Touch Monitors





Overview

The **TDD** curved touch monitors (VESA mount) with C-type / J-type format, Non-LED / LED Framed design and desktop / wall mount installation, which provides impressive visual experience with accurate touch response that is attractive and reliable especially for game players. It is available in a wide range of sizes (23.6" to 55"), offering the versatility in the area of gaming, casino and sports betting.

Features

- Touch (optional for no touch) thru glass enabled with PCAP with Customized LED Tiles for casino slot machines
- Comfortable Viewing Experience with R1500 / R1800 Ratio and 2 / 2.5 /4K Resolution with excellent image clarify

49"(16:9), 124.46cm, Active matrix TFT LCD (LED)

• Outstanding Industrial-grade design with High-end Sturdy Steel / Aluminum Frame

1073.78 mm x 604mm

Specifications

Diagonal Size

Active Area (mm)

	_		_
_	٠.	n	Δ I

Resolution	3840 x 2160 (UHD)		
Viewing Angle	Horizontal: 89° or 178° total / Vertical: 89° or 178° total		
Number of Colors	16.7 million		
Brightness (typical)	500 nits		
Response Time-total	8 (Typ.)(G to G) ms		
Contrast Ratio	1100:1		
Touch			
Touch Technology	PCAP (Projected Capacitive) - 10 Touch Capacity		
Surface Treatment	Water, Dust & Vandal proof; Optional: Anti-glare, Anti-fingerprint, Anti-smudge, Anti-bacterial		
Supported OS	Windows / Android / Linux / Mac		
Others	Hot-bending process / TP Thickness: 4.55mm (±0.3mm) / Light Transmission: ≥85%		
Interfaces / Connectors / Controls			
interfaces / Connec	tors / Controls		
Interfaces & Connectors	HDMI x3 / DP x1 / USB-A x1 / USB-B x1 for Touch / DC x1 / Audio x1; 5 OSD buttons		
Interfaces&Connectors	HDMI x3 / DP x1 / USB-A x1 / USB-B x1 for Touch / DC x1 / Audio x1; 5 OSD buttons RGB colorful effect; atmosphere light mode: solid color, marquee, water, breathing, gradient		
Interfaces&Connectors LED Parameters	HDMI x3 / DP x1 / USB-A x1 / USB-B x1 for Touch / DC x1 / Audio x1; 5 OSD buttons RGB colorful effect; atmosphere light mode: solid color, marquee, water, breathing, gradient mode on the Front / Side / Back(with Programmable Controller)		
Interfaces&Connectors LED Parameters Power	HDMI x3 / DP x1 / USB-A x1 / USB-B x1 for Touch / DC x1 / Audio x1; 5 OSD buttons RGB colorful effect; atmosphere light mode: solid color, marquee, water, breathing, gradient mode on the Front / Side / Back(with Programmable Controller) Supply / Consumption: 100-240 VAC / 12VDC +/- 5%; 142W typical, 1.5W sleep, 0.5W off Product Dimensions: 1152.37 x 684 x 59mm / Weight (Unpacked / Packed): 36 / 41kg		
Interfaces&Connectors LED Parameters Power Mechanical	HDMI x3 / DP x1 / USB-A x1 / USB-B x1 for Touch / DC x1 / Audio x1; 5 OSD buttons RGB colorful effect; atmosphere light mode: solid color, marquee, water, breathing, gradient mode on the Front / Side / Back(with Programmable Controller) Supply / Consumption: 100-240 VAC / 12VDC +/- 5%; 142W typical, 1.5W sleep, 0.5W off Product Dimensions: 1152.37 x 684 x 59mm / Weight (Unpacked / Packed): 36 / 41kg Box Dimensions: 1288 x 827 x 228mm / VESA Mounting: 250 x 260 / 300 x 260mm		

^{*} TDD (www.tddtouch.com, sales@tddtouch.com) reserves the right to change specifications without prior notice.