

# TDD-CP-SOK236MCB-F

23.6" **Slim Curved** Free Standing Self-Ordering Kiosks with Middle Hollow LED



## Overview

The **TDD Self Ordering Kiosks** include **Slim Curved**, **Sleek Curved**, **Slim**, **Easy** and **Android Self-checkout** types, which are designed to adapt to changing consumer demands in retail environments. These modular and reliable kiosks support self-ordering, self-checkout, and visitor check-in, empowering customers to control their experience. Equipped with Receipt Printer, high-precision QR Code reader, ID Camera and optional functions like RFID, Fingerprint scanning, Metal keypads, Bill & Coin Recycler (Custom) and **TDD's** innovative technology, it is the perfect solution for seamlessly integrating modern businesses to these user-friendly kiosks to enhance customer satisfaction and operational efficiency.

## Features

- Robust construction ensures continuous use in unattended areas.
- Modular design minimizes total cost of ownership while maximizing operational efficiency.
- Compact design for space-restricted environments with **middle hollow LED and orange decorative edge strips**

## Specifications

### System (3.5" Motherboard: 5.7 x 4inch=146 x102mm)

Processor	Android: RK3188/RK3288/RK3566/ <b>RK3568</b> Quad-core Cortex-A9/A17/A55 1.6/1.8/ 2.0GHz Windows: Intel® J1900 / J4125 Quad Core 2.0 / 2.7GHz / Intel® Core™ i3 / <b>i5</b> / i7 / i9 4-13 <sup>th</sup> G
Memory(RAM)	Android: 1 / <b>2GB(std)</b> / 4 / 8 / 16GB; Windows: DDR3/4 2 / <b>4(std)</b> / 8 / 16 / 32 / 64GB
Storage	Android: 4/8/ <b>16(std)</b> /32/64GB eMMC Flash; Windows: 32/64( <b>std</b> )/128/256/512GB SSD/HDD

### Panel (Non-LED | LED Framed, C curved, Aluminum | Steel Frame, Curvature: R1500)

Size / Active Area (mm)	23.6"(16:9), 59.944cm, Active matrix TFT LCD (LED) / 521.395 mm x 293.284mm
Resolution / Contrast	1920 x 1080 / 3000:1
Viewing Angle	Horizontal: 89° or 178° total / Vertical: 89° or 178° total
Color Depth/Brightness	16.7 million / 350 nits
Response Time / Freq	10 (Typ.)(Tr+Td) ms / Horizontal: 30 - 60 KHz / Vertical: 50 - 75 Hz

## Touch

Touch Technology / OS	PCAP (Projected Capacitive) - 10 Touch Capacity / Windows / Android / Linux / Mac
-----------------------	---

Surface Treatment	Water, Dust & Vandal proof; <b>Optional:</b> Anti-glare, Anti-fingerprint, Anti-smudge, Anti-bacterial
<b>I / O Ports</b>	
Android	USB x2 / HDMI x1 / LAN x1 / WIFI x1 / DC x1 / TF-CARD x1 / Audio x1
Windows	USB x4 / COM x2 / VGA x1 / HDMI x1 / LAN x1 / WIFI x1 / DC x1 / Audio x1 / Mic x1
<b>Power</b>	Supply / Consumption: 100-240 VAC / 12VDC 5A +/- 5%; 25W typical, 1.2W sleep, 0.5W off
<b>Mechanical</b>	Product Dimensions (HxWxD): N/Amm/Weight(Unpacked/Packed): N/A kg Box Dimensions: N/A mm / VESA Mounting: N/A
<b>Environmental</b>	Operating / Storage Temperature: -10°C to 50°C / -20°C to 60°C
<b>Accessories</b>	Power adapter / cable, free standing / wall mount mounting kits w/screws (opt.)
<b>Others</b>	MTBF / Warranty / Enclosure Color / Ready for Use: 50,000 hours / 1-year / white black / 24/7 <b>Speakers:</b> Internal, 8Ω / 2W x 2
<b>Optional Peripherals</b> (Default: Marked by Yellow)	<b>Receipt Printer:</b> thermal, 150mm/s, 80mm printing width, auto cut, paper end detection, USB <b>QR / Barcode Scanner:</b> 1D / 2D, CMOS with <b>640 x 480 (opt. for 752 x 480)</b> pixel, USB <b>ID Camera:</b> 2 / 5MP , monocular / <b>binocular</b> cameras, USB <b>RFID:</b> 13.56M Hz Mifare ISO14443A read only, USB <b>POS Holer:</b> Yes <b>Fingerprint Scanner:</b> Custom, USB <b>Metal Keypad:</b> Custom, 16 keys, USB <b>4G:</b> Mini-PCle, <b>GPS:</b> TTL / USB or <b>4G &amp; GPS:</b> Mini-PCle
<div>  <p>Thermal Printer</p> </div> <div>  <p>Barcode Scanner</p> </div> <div>  <p>Camera</p> </div> <div>  <p>RFID Card Reader</p> </div> <div>  <p>Fingerprint Sensor</p> </div> <div>  <p>Keyboard</p> </div> <div>  <p>WIFI Antenna</p> </div> <div>  <p>4G LTE Module</p> </div> <div>  <p>GPS</p> </div> <div>  <p>More Peripherals</p> </div>	

## Dimensions