

TDD-OFTM-BF320HO

32" **Outdoor** Bezel-free (Rear Mount) Open Frame PCAP Touch Monitors



Overview

The **TDD Touch Monitors** include **Standard, Industrial (Open Frame Bezel-free | Rear Mount, Panel Mount, Closed Frame), Outdoor, Waterproof, Stainless Steel, Marine, Curved, Desktop POS, Commercial Displays, Medical and Custom** types, delivers an industrial, reliable and cost-effective solution with outstanding image clarity & accurate touch response for OEMs & systems integrators. 7-98" sizes with rugged bezel, flat structure, high durability and versatility for Kiosks applications from Self-service, Automated Parking, Industrial Automation, Outdoor Control, Healthcare to Gaming.

Features

- Touch thru glass (with **AG & UV Filter**) enabled with PCAP supports thickness up to 5mm
- Embedded design with **Rugged High Bright TFT Panel&Auto-dimmer, Sturdy Aluminum Front Frame&Steel Back**
- IP65 (front) for water and **Dust Protection with Smart Fans**, flexible mounting in any table, kiosk, or cabinet design

Specifications

Panel

Diagonal Size 32"(16:9), 81.28cm, Active matrix TFT LCD (LED)

Active Area (mm) 708.48 mm x 398.52 mm

Resolution 1920 x 1080

Viewing Angle Horizontal: 89° or 178° total / Vertical: 89° or 178° total

Number of Colors 16.7 million

Brightness (typical) **1000 nits**

Response Time-total 8 (Typ.)(G to G) ms

Contrast Ratio 1200:1

Input Video Frequency Horizontal: 30 - 60 KHz / Vertical: 50 - 75 Hz

Touch

Touch Technology PCAP (Projected Capacitive) - 10 Touch Capacity (**Optional: Waterproof Firmware**)

Surface Treatment Water, Dust & Vandal proof; **Optional:** Anti-glare, Anti-fingerprint, Anti-smudge, Anti-bacterial

Supported OS Windows / Android / Linux / Mac

Interfaces / Connectors / Controls

Video Interfaces VGA x1 / HDMI x1 / DVI x1 (opt.) / Display Port x1 (opt.) / USB x1 for Touch; HDCP: Yes

Connectors & Controls Audio Mini jack x1 / DC x1; 5 OSD buttons

Power

Supply / Consumption: 100-240 VAC / 12VDC +/- 5%; 47W typical, 1.5W sleep, 0.5W off

Mechanical

Product Dimensions: 773.5 x 468.2 x 82.5mm / Weight (Unpacked / Packed): 23 / 28 kg
Box Dimensions: 950 x 218.5 x 640mm / VESA Mounting: 200 x 200mm

Environmental

Operating / Storage Temperature: **-20°C to 70°C**

Accessories

Power adapter / cable, HDMI / VGA / Touch USB cable, flush mount brackets w/screws (opt.)

Others

MTBF / Warranty / Enclosure Color: 50,000 hours demonstrated / 1-year / black | silver
Ready for Use: 24/7

* TDD (www.tddtouch.com, sales@tddtouch.com) reserves the right to change specifications without prior notice.