TDD-OFTM-BF121 12.1" Bezel-free Open Frame PCAP Touch Monitors





Overview

The **TDD** open frame touch monitors include bezel-free & flat bezel types with PCAP or resistive touch technology, which delivers an industrial & reliable solution with outstanding image clarity and accurate touch response that is cost-effective for OEMs and systems integrators. Embedded eye-catching and rugged bezel with flush front finish structure delivers flat design with high durability and scratch & water resistance. It is available in a wide range of sizes (7" to 55"), offering the versatility for embedded kiosk applications from self-service, gaming, industrial automation to digital signage & healthcare.

Features

- Touch thru glass enabled with PCAP supports thickness up to 5mm
- Embedded design with sturdy metal or aluminum (optional for back) enclosure
- IP65 (front) for water and dust protection; Flexible mounting in any table, kiosk, or cabinet design

Specifications

Panel

Diagonal Size	12.1"(4:3), 30.73cm, Active matrix TFT LCD (LED)
Active Area (mm)	246 mm x 184.5 mm
Resolution	800 x 600
Viewing Angle	Horizontal: 85° or 170° total / Vertical: 85° or 170° total
Number of Colors	16.7 million
Brightness (typical)	Panel: 300 nits / With PCAP Touch: 265 nits
Response Time-total	25 msec typical
Contrast Ratio	700:1
Input Video Frequency	Horizontal: 30 - 60 KHz / Vertical: 50 - 75 Hz
Touch	
Touch Technology	PCAP (Projected Capacitive) - 10 Touch Capacity
Surface Treatment	Water, Dust & Vandal proof, Anti-glare; Anti-fingerprint, Anti-smudge, Anti-bacterial (optional)
Supported OS	Windows / Android / Linux / Mac
Interfaces / Connectors / Controls	
Video Interfaces	VGA x1 / HDMI x1 / DVI x1 / Display Port x1 (optional)/ USB x1 for Touch; HDCP: Yes
Connectors & Controls	Audio Mini jack x1 / DC x1; 5 OSD buttons
Power	Supply / Consumption: 100-240 VAC / 12VDC +/- 5%; 12.2W typical, 1.5W sleep, 0.5W off
Mechanical	Sizes & Weight / Mount: 275.69mm x 214.29mm x 39.2mm / 1.2 kg unpackaged; 75 / 100mm
Environmental	Operating Temperature: 0°C to 50°C
Accessories	Power adapter / cable, HDMI / VGA / Touch USB cable, Flush Mount Brackets w/Screws
Others	MTBF / Warranty / Enclosure Color: 50,000 hours demonstrated / 1-year / black
* TDD (<u>www.tddtouch.com</u> , <u>sales@tddtouch.com</u>) reserves the right to change specifications without prior notice.	