# TDD-OFTM-BF156 15.6" Bezel-free Open Frame PCAP Touch Monitors





### Overview

The **TDD** open frame touch monitors include bezel-free & flat bezel types with PCAP or resistive touch technology, which delivers an industrial & reliable solution with outstanding image clarity and accurate touch response that is cost-effective for OEMs and systems integrators. Embedded eye-catching and rugged bezel with flush front finish structure delivers flat design with high durability and scratch & water resistance. It is available in a wide range of sizes (7" to 55"), offering the versatility for embedded kiosk applications from self-service, gaming, industrial automation to digital signage & healthcare.

#### Features

- Touch thru glass enabled with PCAP supports thickness up to 5mm
- Embedded design with sturdy metal or aluminum (optional for back) enclosure
- IP65 (front) for water and dust protection; Flexible mounting in any table, kiosk, or cabinet design

## Specifications

### **Panel**

iagonal Size15.6"(16:9), 39.5cm, Active matrix TFT LCD (LED)ctive Area (mm)344 mm x 194 mmesolution1920 x 1080ewing AngleHorizontal: 85° or 170° total / Vertical: 85° or 170° totalumber of Colors16.7 million
esolution1920 x 1080ewing AngleHorizontal: 85° or 170° total / Vertical: 85° or 170° total
ewing Angle Horizontal: 85° or 170° total / Vertical: 85° or 170° total
umber of Colors 16.7 million
rightness (typical) Panel: 250 nits / With PCAP Touch: 215 nits
esponse Time-total 10 msec typical
ontrast Ratio 500:1
put Video Frequency Horizontal: 30 - 60 KHz / Vertical: 50 - 75 Hz
ouch
buch Technology PCAP (Projected Capacitive) - 10 Touch Capacity
urface Treatment Water, Dust & Vandal proof, Anti-glare; Anti-fingerprint, Anti-smudge, Anti-bacterial (optional)
upported OS Windows / Android / Linux / Mac
iterfaces / Connectors / Controls
deo Interfaces VGA x1 / HDMI x1 / DVI x1 / Display Port x1 (optional)/ USB x1 for Touch; HDCP: Yes
onnectors & Controls Audio Mini jack x1 / DC x1; 5 OSD buttons
ower Supply / Consumption: 100-240 VAC / 12VDC +/- 5%; 20W typical, 1.5W sleep, 0.5W off
echanical Sizes & Weight / Mount: 385.59mm x 235.59mm x 39.2mm / 3 kg unpackaged; 75 / 100mm
nvironmental Operating Temperature: 0°C to 50°C
ccessories Power adapter / cable, HDMI / VGA / Touch USB cable, Flush Mount Brackets w/Screws
thers MTBF / Warranty / Enclosure Color: 50,000 hours demonstrated / 1-year / black
<b>TDD</b> ( <u>www.tddtouch.com</u> , <u>sales@tddtouch.com</u> ) reserves the right to change specifications without prior notice.